Valve systems → Standardized valve systems

5/3-way valve, Series 581, size 2

► Qn = 2100 l/min ► plate connection ► compressed air connection output: Base plate ISO 5599-1 ► Can be assembled into blocks ► suitable for ATEX

00132220

Standards	ISO 5599-1
ATEX	2G Ex mb II T42D Ex tD A21 T130°C
Version	Spool valve
Sealing principle	soft sealing
Blocking principle	Single base plate principle
Working pressure min./max.	-0.95 bar / 16 bar
Ambient temperature min./max.	-20°C / +70°C
Medium temperature min./max.	-20°C / +70°C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 mg/m³ - 5 mg/m³
Pneumatic ports	Base plate ISO 5599-1
Mounting screw	with hexagon socket
mounting screw tightening torque	3.5 Nm
Materials:	
Housing	Aluminum
Seals	Acrylonitrile Butadiene Rubber

Technical Remarks

- The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C.
- The oil content of air pressure must remain constant during the life cycle.
- Use only the approved oils from Bosch Rexroth, see chapter „Technical information“.

	Flow conductance	Qn	Control pressure min./max.	Weight	Note	Part No.
	C					
	[l/(s*bar)]	[l/min]	[bar]	[kg]		
	9.6	2100	3 / 16	0.42	-	**5812430000**
	9.6	2100	3 / 16	0.42	1)	**5812431000**
	9.6	2100	3 / 16	0.42	-	**5812530000**
	9.6	2100	3 / 16	0.42	1)	5812531000
	9.6	2100	3 / 16	0.42	-	5812730000
	9.6	2100	3 / 16	0.42	1)	5812731000

1) with throttle
Nominal flow Qn at 6 bar and Δp = 1 bar

Valve systems → Standardized valve systems

5/3-way valve, Series 581, size 2

► Qn = 2100 l/min ► plate connection ► compressed air connection output: Base plate ISO 5599-1 ► Can be assembled into blocks ► suitable for ATEX

Dimensions