Valve systems → Supplementary products

5/2-way valve, Series 581, size 4

► Qn = 6000 l/min ► plate connection ► Pilot valve width: 30x22 mm CNOMO ► compressed air connection output: Base plate ISO 5599-1 ► Electr. connection: Plug, ISO 4400, form A ► Manual override: without

00133532

Standards	ISO 5599-1
Version	Spool valve
Sealing principle	soft sealing
Blocking principle	Single base plate principle
Working pressure min./max.	See table below
Ambient temperature min./max.	-15°C / +50°C
Medium temperature min./max.	-15°C / +50°C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 mg/m³ - 5 mg/m³
Pneumatic ports	Base plate ISO 5599-1
Protection classwith electrical connector/ plug	IP 65
Duty cycle	100 %
Switch-on time	21 ms
Switch-off time	21 ms
Mounting screw	with hexagon socket
mounting screw tightening torque	10 Nm
Materials:	
Housing	Aluminum
Seals	Acrylonitrile Butadiene Rubber

Technical Remarks

- The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C.
- The oil content of air pressure must remain constant during the life cycle.
- Use only the approved oils from Bosch Rexroth, see chapter „Technical information“.

Operating voltage		Voltage tolerance		Power consumption	Switch-on power	Holding power
DC	AC 50 Hz	DC	AC 50 Hz	DC	AC 50 Hz	AC 50 Hz
				W	VA	VA
24 V	-	-10% / +10%	-10% / +10%	6.7	-	-
-	230 V	-	-10% / +10%	-	15.2	10.8

	Operating voltage		Flow con-ductance	Qn	Working pressure min./max.	Control pressure min./max.	Weight	Note	Part No.
	DC	AC 50 Hz	C						
			[l/(s*bar)]	[l/min]	[bar]	[bar]	[kg]		
	24 V -	- 230 V	24.5	6000	1.5 / 16	1.5 / 16	1.57	1)	5814290530 5814290430
	24 V -	- 230 V	24.5	6000	1.5 / 16	1.5 / 16	1.57	1); 3)	5814291530 5814291430

1) Pilot: internal
2) Pilot: external
3) with throttle
Nominal flow Qn at 6 bar and Δp = 1 bar

Valve systems → Supplementary products

5/2-way valve, Series 581, size 4

► Qn = 6000 l/min ► plate connection ► Pilot valve width: 30x22 mm CNOMO ► compressed air connection output: Base plate ISO 5599-1 ► Electr. connection: Plug, ISO 4400, form A ► Manual override: without

	Operating voltage		Flow conductance	Qn	Working pressure min./max.	Control pressure min./max.	Weight	Note	Part No.
	DC	AC 50 Hz	C						
			[l/(s*bar)]	[l/min]	[bar]	[bar]	[kg]		
	24 V -	- 230 V	24.5	6000	-0.95 / 16	1.5 / 16	1.57	2)	5814292530 5814292430
	24 V -	- 230 V	24.5	6000	-0.95 / 16	1.5 / 16	1.57	2); 3)	5814293530 5814293430

1) Pilot: internal
2) Pilot: external
3) with throttle
Nominal flow Qn at 6 bar and Δp = 1 bar

Dimensions