



TRANSPORTATION CERTIFICATE

Ref. TC – LS14500- 09/2015 - 14

This is to certify that the following Saft cell **LS14500** has met the requirements of the UN Recommendations on the transport of dangerous goods, Part III, sub-section 38.3, Manual of Tests and Criteria.

Products covered by this certificate	
Tested product P/N	04224X
Products P/N by assimilation	All the following LS 14500 cell versions that just vary by their termination mode and labeling.

Product description	
Technology	Primary (non-rechargeable Lithium-Thionyl chloride (Li-SOCl ₂) cell
Description	Primary AA-sized single cell
Nominal Voltage	3.6V
Nominal Capacity	2.6 Ah
Lithium metal content	0.7 g

	Results	Report number
38.3.4.1 Test 1: Altitude Simulation	Passed	T0336-14
38.3.4.2 Test 2: Thermal test	Passed	T0336-14
38.3.4.3 Test 3: Vibration	Passed	T0336-14
38.3.4.4 Test 4: Shock	Passed	T0336-14
38.3.4.5 Test 5: External short circuit	Passed	T0336-14
38.3.4.6 Test 6: Impact/crush (cell test)	Passed	T0404-13
38.3.4.7 Test 7: Overcharge	Not applicable for primary battery	
38.3.4.8 Test 8: Force-discharge (cell test)	passed	T0336-14

Product Classification

This lithium battery and/or cell meets the criteria and requirements of the relevant sections of the **UN Manual of Tests and Criteria** and is assigned for transportation to **UN 3090** in accordance with the current **UN Recommendations on the Transport of Dangerous Goods Model Regulations**.

Signed on Behalf of Saft, Specialty Battery Group

Pascal Foucoin Lithium Division Quality Mgr

Dated

P/O

Marielle Le Dantec Lithium Division Quality Customer

Dated

29/09/15